

H&H PROMOTIONS

CONTACTS FOR RULE QUESTIONS

TODD HOLLINGER 937-539-6114 TOBY HIGHLEY 937-684-5422

TOBY FRATER 937-407-1097

BONE STOCK CLASS

BONE STOCK RULES 1980 & NEWER CARS ONLY

1. **MUST BE 100% STOCK**, entire drive train must be same make as car (Chevy to Chevy ford to ford and so on) Must appear to be factory engine to car with stock exhaust.
2. Engine must be mounted with stock mounts in stock position. No welding of mounts bolted only. No homemade cross members, cross members must be stock and bolted in not welded
3. Doors must be chained or wired. No more than 6 places.
4. Trunks must be chained or wired. No more than 4 places. **TRUNKS MUST BE OPEN DURING INSPECTION!** Car must have deck lid and or tailgate No welding or adding metal. Trunk lid must be in stock location. No tucking, wedging, pre bending, smashing, folding or anything else you can think of. No welding washers for holes.
5. Hoods may be wired or chained in 4 spots. X chain or 2 strands per hole. It must be sheet metal to sheet metal only. No welding washers for holes. Must be 12" hole in hood in case of fire. Remove hood latch!!! Hood must be open for inspection.
6. .Must use D.O.T. tires **DOUBLES PERMITTED**, no tractor, implement, or foam filled tires no valve stem protectors
7. You may leave stock gas tank in stock location or you may relocate the fuel tank to rear floor of car if this is done you must use a fuel cell or boat tank no stock fuel tanks permitted inside of car. Must only have 3 gallons of gas. You may be asked to drain it if the gauge doesn't work.
8. Windshield may be left in car, **WE RECOMEND WINDSHIELD BE REMOVED!**
9. The following must be removed prior to entering the fairgrounds, windows , headlights, taillights, all chrome and mirrors. Interior must be swept clean of debris and glass.
10. Stock type springs and shocks. No solid suspension. No spring risers, wire, chains or any weld on rear ends or rear spring pockets. Cars must bounce & cars must be **STOCK!!!!**
11. **YOU MAY WELD SPIDER GEARS IN REAR END TO MAKE IT POSI. NO GEARS OR AFTERMARKET AXLES PERMITTED**
- 12 Paint front doors in contrasting paint. Example if the car is black paint doors white
13. Do not strip under the hood. Battery **MAY** be **LEFT** in stock location. But you **MUST** put rubber mat over it or spray foam around it not excessively **BATTERY MUST BE SECURELY FASTENED**. Do not spray foam on anything else. **YOU MAY MOVE THE BATTERY TO THE FLOOR OF THE CAR YOU MAY LENGTHEN CABLES TO THE REACH BATTERY ON FLOOR NOT THE WIREING HARNESS CAR MUST START WITH FACTORY IGNITION THIS WILL BE STRICKLY ENFORCED**
14. **YOU MAY USE AN 80 & NEWER BUMPER ON CAR THEY MUST BOLT ON IN FACTORY LOCATION AND MANNER YOU MAY WELD WITH 4 1" WELDS ON THE SHOCK PLATE TO BUMPER**
15. Read all rules carefully and follow them! It will be a cheap easy build. Any questions call!
There will be no stretching or bending of any rules or you will either run in the modified class or go home.